

Technology for cable laying and overhead power lines

- Energy cable laying up to 680 kV
- Fibre optic, mini and micro cables
- Cable winding and length measuring
- Overhead line construction up to 110 kV
- Seminars and product instructions



Conduit calibre



Conduit calibre of polyamide. The calibre diameter should be approx. 80-95 % of the nominal internal diameter of the duct. Please ask your customer which calibre diameter he expects.

Code	Type	OD	D-ID	Calibre-L	Total-L	kg
231270	KDP 50/36	36	40-45	110	190	0,30
231280	KDP 63/45	45	51-56	150	230	0,45
231290	KDP 75/55	55	61-71	200	300	0,85
231310	KDP 90/65	65	74-84	200	300	1,00
231350	KDP 110/85	85	90-104	200	310	1,10
231360	KDP 110/90	90	100-104	200	310	1,20
231380	KDP 125/95	95	102-104	250	350	1,60
231400	KDP 125/105	105	113-118	250	350	2,10
231410	KDP 140/115	115	126-132	250	350	3,10
231420	KDP 150/125	125	134-144	250	350	3,60
231425	KDP 160/130	130	134-150	250	350	3,90
231430	KDP 160/135	135	144-155	250	350	3,40
231450	KDP 180/150	150	160-170	250	350	5,00
231460	KDP 200/165	165	180-190	250	350	6,00
231470	KDP 225/185	185	200-225	250	360	7,30